

Morrison ExStream Water Softener

Quick Start-Up Guide:

- 1- Leave Bypass valves closed. Check water pressure before installation. High water pressure will damage your system & void the warranty. The warranty states a MAX of 90-psi. If your water pressure is any higher than 80-psi we recommend installing a new PRV valve (pressure reducing valve) to protect your equipment. Check plumbing to make sure the Softener has not been plumbed in BACKWARDS. When facing the softener, the Inlet/raw water is on the RIGHT, Out-let/Soft water is on the LEFT. See arrows on valve body.**
- 2- Plug power cord into power outlet. The time of day will be flashing. PRESS the CLOCK button. Use the UP & DOWN arrow buttons & the NEXT button to set the correct TIME OF DAY. Once time of day is set correctly, press the NEXT Button.**
- 3- PRESS & HOLD the NEXT button & the UP arrow button at the SAME TIME until the “Hardness” setting is showing, then release the buttons. We Pre-Set the HARDNESS setting at “20” Grains Hard. Use the UP & DOWN arrow buttons to set the proper incoming water Hardness, then press the NEXT button. If you do not know the incoming water hardness then test it with a hardness test kit or have it tested for you. (NOTE: It is VERY important to set the hardness setting correct for what the incoming water hardness is, failure to do so will result in improper softening capacity). Once Proper HARDNESS is set, press the Next Button. Here you can set the Calendar Override & Regeneration time. (We pre-set the Calendar Override to 0, meaning it is inactivated. We set the Regeneration time at 2:00 AM). Make any changes then press the NEXT button until Time of Day is showing.**
- 4- Start the Softener into a Manual Regeneration to flush the resin and relieve the air out of the tank. Press & HOLD the REGEN button for 3 seconds until the valves starts into “BACKWASH” & release the button. Open the In-coming, red handled bypass knob ½ of the way open (right knob). Once you see water running to the Drain, OPEN the red handled knob fully open. Let the Softener flush in this cycle for 6 minutes, then press the REGEN button again and release. The control will say “BRINE 60 minutes”, press the REGEN button again, the control will say “2 BACKWASH”, press the REGEN button again, the control will say “RINSE”, leave in this position for 2 minutes then press the REGEN button again, the control will say “FILL”. Leave the Softener in the FILL position & open up the OUT-LET red handled bypass knob (left knob) fully open.**
- 5- Start-Up is now complete. The water Softener will automatically FILL the Brine Tank with proper water & return itself to the service position. Any questions, please call the factory. 801-785-7010**